



SolarEdge Single Phase Inverters

SE2200H, SE3000H, SE3500H, SE3680H
SE4000H, SE5000H, SE6000H



INVERTERS

Optimized installation with HD-Wave technology

- Specifically designed to work with power optimizers
- Record-breaking efficiency
- Extremely small, lightweight and easy to install
- High reliability without any electrolytic capacitors
- Built-in module-level monitoring
- Outdoor and indoor installation
- Compatible with the StorEdge Interface for Smart Energy Management StorEdge™ applications





Single Phase Inverters

SE2200H, SE3000H, SE3500H, SE3680H
SE4000H, SE5000H, SE6000H

	SE2200H	SE3000H	SE3500H	SE3680H	SE4000H	SE5000H	SE6000H		
OUTPUT									
Rated AC Power Output	2200	3000	3500	3680	4000	5000 ⁽¹⁾	6000	VA	
Maximum AC Power Output	2200	3000	3500	3680	4000	5000 ⁽¹⁾	6000	VA	
AC Output Voltage (nominal)	220 / 230							Vac	
AC Output Voltage Range	184 - 264.5							Vac	
AC Frequency (nominal)	50 / 60 ± 5							Hz	
Maximum Continuous Output Current	10	14	16	16	18.5	23	27.5	A	
Residual Current Detector / Residual Current Step Detector	300 / 30							mA	
Utility Monitoring, Islanding Protection, Country Configurable Thresholds	Yes								
INPUT									
Maximum DC Power	3400	4650	5425	5700	6200	7750	9300	W	
Transformer-less, Ungrounded	Yes								
Maximum Input Voltage	480							Vdc	
Nominal DC Input Voltage	380							Vdc	
Maximum Input Current	6.5	9	10	10.5	11.5	13.5	16.5	Adc	
Reverse-Polarity Protection	Yes								
Ground-Fault Isolation Detection	600kΩ Sensitivity								
Maximum Inverter Efficiency	99.2							%	
European Weighted Efficiency	98.3	98.8				99		%	
Nighttime Power Consumption	< 2.5							W	
ADDITIONAL FEATURES									
Supported Communication Interfaces	RS485, Ethernet, ZigBee (optional), WiFi (optional), Cellular (optional)								
Smart Energy Management	Export Limitation, StorEdge applications								
STANDARD COMPLIANCE									
Safety	IEC-62109-1/2, AS-3100								
Grid Connection Standards	AS-4777, VDE-AR-N-4105, VDE 0126-1-1, UTE C15-712, G83/2, G59/3, CEI-021, EN 50438, IEC61727, IEC62116, ÖNORM, TF3.2.1, C10-11, NRS 097-2-1								
Emissions	IEC61000-6-2, IEC61000-6-3, IEC61000-3-11, IEC61000-3-12, FCC Part 15 Class B								
INSTALLATION SPECIFICATIONS									
AC Output - Supported Cable Diameter	9 - 16							mm	
AC - Supported Wire Cross Section	1 - 16							mm ²	
DC Input	1 x MC4			2 x MC4 pair					
Dimensions (H x W x D)	280 x 370 x 142							mm	
Noise	< 25							dB(A)	
Weight	9.5							kg	
Cooling	Natural Convection								
Operating Temperature Range	-20 to +60 ⁽²⁾ (-40°C option)							°C	
Protection Rating	IP65 - Outdoor and Indoor								

⁽¹⁾ 4600VA in Germany
⁽²⁾ De-rating from 50°C



RoHS

